

Cee-Bee® E-2012A

Cee-Bee® E-2012A is an environmentally friendly paint stripper designed for removing paint from selectively strippable coating systems such as those used on composite aircraft.

Conforms To

- Airbus
 - CML 12-013A
 - Application Code: 09ABB1
 - Product Code: 960300
 - Ref. Item 12-013A
- Boeing
 - BMS 11-13 (QPL)

Benefits

- Contains no halogenated solvents, phenol, heavy metals or other toxic materials (per Proposition 65).
- Provides excellent removal of topcoats over selectively strippable coatings.
- Thixotropic. Clings to vertical, inclined and overhead surfaces.
- Slow drying for a long reaction time.
- Free rinsing.
- Safe on all aircraft structural metals, including high strength steel.
- Surfactants are biodegradable.

Properties

- Thick, opaque liquid
- Mild ammonia odor

Notes Prior to Handling

Before using your Cee-Bee® products, all safety and operating instructions should be read and understood. If you have any questions, please contact your Cee-Bee® representative before proceeding.

Use Procedure

- Use a high pressure 10:1 or 5:1 air-activated pump equipped with a 1/2" I.D. high pressure hose and spray wand with a fan type spray nozzle. Examples of the type of pump acceptable for this application are Graco 5:1 air activated pumps, Model 205-997 or 224-350.
- It is very important to use the correct type of spray nozzle for this application. Spray nozzle no. 6508, fan-type is recommended.
- It is also very important to apply the stripper at the correct pressure. Use a pump inlet pressure of 80 to 110 P.S.I. Optimum performance is attained at a temperature of about 75 to 87°F (24 to 31°C).

Paint Removal Procedure

1. The surface to be stripped should be thoroughly clean and free from water.
2. Spray on a light coat of Cee-Bee[®] E-2012A starting from the bottom of the aircraft and working upward. Apply Cee-Bee[®] E-2012A as evenly as possible.
3. Keep the surface wet with Cee-Bee[®] E-2012A until the paint buckles.
4. When the paint is lifted (one hour to overnight for tough coatings), brush the surface thoroughly to remove the loosened paint.
5. Reapply Cee-Bee[®] E-2012A as required to loosen any remaining paint.
6. When all the paint has been lifted, use a brush or squeegee to remove the loosened paint and residual paint remover.
7. Thoroughly rinse the surface with high-pressure water.

Safety, Handling, and Precautions

- Some form of eye protection is always essential when working with any chemical.
- Product may irritate eyes and skin. Use goggles, gloves and other protective clothing sufficient to avoid contact.
- Concentrated vapors may cause irritation.
- Use in well ventilated area.
- For contact with eyes or skin, flood with water immediately. Seek medical attention if irritation persists.
- Proper attention should always be paid to environmental considerations.

Contact Us

United States

McGean

Phone: +1-216-441-4900

Fax: +1-216-441-1377

Email: Aviation@McGean.com

United Kingdom

McGean-Rohco (UK) Ltd.

Phone: +44-1902-456563

Fax: +44-1902-457443

Email: Aviation@McGean-Rohco.co.uk

Singapore

McGean Singapore

Phone: +65-6863-2296

Fax: +65-6863-2297

Email: Info@ceebee.com.sg

China

Cee-Bee Aviation Materials (Xiamen) Co. Ltd.

Phone: +86-592-551-3689

Email: Info@ceebee.com.cn

Cee-Bee[®] E-2012A is an environmentally friendly paint stripper designed for removing paint from selectively strippable coating systems such as those used on composite aircraft.

CAUTION: BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE INFORMATION CONTAINED IN MCGEAN'S SAFETY DATA SHEETS. All information contained therein or in this document regarding handling, personal protection, and other safety measures must be followed during use. McGean presents the information herein without warranty and disclaims any liability, including any consequential, special, or indirect damages, arising from its use and misuse. Because the use, the conditions of use, product or product composition, and/or applicable laws may differ from one location to another and/or may change with time, the purchaser and/or user is solely responsible for determining whether the product is appropriate for use. McGean recommends use of this product solely in commercial processes which are specified by McGean and which do not violate any third-party patent rights or any laws or regulations or otherwise adversely impact human health and the environment. Users must make their own investigations and determine the suitability of the product for their particular purposes. McGean does not guarantee the accuracy of any data provided by its suppliers. MCGEAN MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM. USE OF ANY MCGEAN PRODUCT IS AT THE USER'S RISK.



Revision: 06/2021 (Rev. A2)